

Mantra Mini Specifications

control

up to 48 fixtures on 1024 DMX slots

up to 100 active simultaneous cues

massive memory - over 1000 shows can be stored internally

play default cues on power-up

status logging and reporting

remote app for Windows and MAC-based devices allowing loading, editing and storing of show information

UDP, TCP/IP and OSC interface for remote controlling by 3rd party control panels

inputs

DMX512 (1990) and DMX512-A (E1-11)

USB port for show data upload/backup and software upgrades

three isolated contact closure inputs via 2-pole plug-in screw terminals for fire, emergency or playing cues

live console override via Art-Net or sACN

UDP via Ethernet for third-party remote control

outputs

dual DMX512 outputs via two 3-pole plug-in screw terminals

Art-Net and sACN outputs via Ethernet connection

room linking via Ethernet, requires one Mantra Mini per room

expansion port for future proofing

power

PoE (via RJ45 Ethernet connector) or 9-24V DC (20W max) supply via 2-pole plug-in screw terminals
(external power supply not included)

mechanicals

158mm (w) x 59mm (d) x 104mm (h)

weight: 350g

TS-35 DINrail-mount, high-strength, flame-retardant ABS plastic chassis

CE (European) and RCM (Australian) approved

**peace of
mind**

two-year warranty

designed and manufactured in Australia by LSC, an Australian-owned company with over 40 years' experience in developing world-first products